

IN THE CLAIMS

This listing of the claims replaces all prior listings of claims.

1. (Currently Amended) An organic electroluminescence display having active-matrix circuitry, the organic electroluminescence display comprising:

a substrate;

a device layer provided on the substrate, the device layer comprising a plurality of luminescent devices defining pixel units arrayed in a matrix, each luminescent device having an emitting area that emits independently of the emitting areas of the other luminescent devices;

a circuitry layer provided between the substrate and the device layer, the circuitry layer comprising pixel circuits for driving the respective luminescent devices, the pixel circuits defining the pixel units; and

contacts electrically connecting each of the luminescent devices with a corresponding pixel circuit, wherein the contacts are provided between adjacent emitting areas of the luminescent devices and between adjacent upper pixel electrodes that each cover a respective one of the emitting areas.

2. (Previously Presented) An organic electroluminescence display according to Claim 1, wherein the contacts are arrayed in a single dimension for each row or column in the matrix.

3. (Previously Presented) An organic electroluminescence display according to Claim 2, wherein the contacts for the pixel units belonging to two adjacent rows or columns in the matrix are arrayed in a single dimension between the two adjacent rows or columns.

4. (Previously Presented) An organic electroluminescence display according to Claim 1, wherein the luminescent devices are organic electroluminescence devices, each comprising a first electrode, a second electrode, and an organic layer including a luminescent layer and lying between the first electrode and the second electrode.

5. (Previously Presented) An organic electroluminescence display according to Claim 1, wherein the pixel circuits each comprise a thin-film transistor.

6. (Currently Amended) An organic electroluminescence display having active-matrix circuitry, the organic electroluminescence display comprising:

a substrate;

a device layer provided on the substrate, the device layer comprising a plurality of luminescent devices defining pixel units, each luminescent device comprising a lower electrode, an upper electrode, and an organic light emitting layer provided between the upper electrode and the lower electrode, that emits independently of the emitting areas of the other luminescent devices; and

a circuitry layer provided between the substrate and the device layer, the circuitry layer comprising pixel circuits for driving the respective luminescent devices, the pixel circuits defining the pixel units;

wherein each lower electrode has a contact electrically connecting the corresponding luminescent device with the corresponding pixel circuit, and

wherein the contact is provided between adjacent emitting areas of the luminescent devices and between adjacent upper pixel electrodes that each cover a respective one of the emitting areas.

7. (Previously Presented) An organic electroluminescence display according to Claim 6, wherein the pixel circuits each comprise a thin-film transistor.

8. (New) An organic electroluminescence display having active-matrix circuitry, the organic electroluminescence display comprising:

a substrate;

a device layer provided on the substrate, the device layer comprising a plurality of luminescent devices defining RGB subpixel units, each luminescent device having an emitting layer comprised of different materials corresponding to the RGB subpixel units and having an emitting area that emits independently of the emitting areas of the other luminescent devices;

a circuitry layer provided between the substrate and the device layer, the circuitry layer comprising pixel circuits for driving the respective luminescent devices, the pixel circuits defining the pixel units; and

contacts electrically connecting each of the luminescent devices with a corresponding pixel circuit, wherein the contacts are provided between adjacent emitting areas of the luminescent devices and wherein at least one contact is provided for each of the luminescent devices.